

PIH302/ PT300 SCANNER & PTZ405 / PTZ3056 CONTROLLER

PIH302

Indoor Pan / Tilt Scanner



	PIH302
Angular	Pan 0° ~ 350°, Tilt ±60°
Limited Stop	Externally adjustable
Speed Variable	PAN 6° per sec., TILT 4° per sec.
Reversing	Instantaneous
Temp. Range	-5°C ~ 65°C
Input Voltage	24VAC or 117VAC or 240VAC
Limited Switches	PAN and TILT are 15A 10million cycle rating
Cable Requirement	6 conductor unshielded
Connector Socket	8 pin
Construction	Die casting aluminum housing and steel
Finish	Ivory-white baked enamel
Bearings	Throughout baked enamel
Gears	Hardened steel
Seals	Rubber ring and gasket seals for all weather environmental protection
Dimensions	178(L) x 133(W) x 162(H)mm
Weight	2.2kgs

PT300

Outdoor Pan / Tilt Scanner



	PT300
Angular	Pan 0° ~ 350°, Tilt ±90°
Limited Stop	Externally adjustable
Speed Variable	PAN 3° ~ 12° per sec. Tilt 1.8° ~ 6° per sec.
Reversing	Instantaneous
Temp. Range	-26°C ~ 65°C
Input Voltage	120VAC or 240VAC
Limited Switches	PAN and TILT are 15A 10million cycle rating
Cable Requirement	7 conductor unshielded
Connector Socket	8 pin
Construction	Die casting aluminum housing and steel
Finish	Ivory-white baked enamel
Bearings	Throughout baked enamel
Gears	Hardened steel
Seals	Rubber ring and gasket seals for all weather environmental protection
Dimensions	266(H) x 247(W) x 153(D)mm
Weight	10.0kgs

SOLE AGENT:

PTZ405
1CH PTZ Controller



	PTZ405
Input Power Source	230V / 60Hz
Pan / Tilt Manual Control	Joystick up down left right
Pan Auto Manual Control	Rocker switch auto / manual
Pan / Tilt Connectors	6 Pins screw terminal blocks 1.auto 2.left 3.right 4.common 5.up 6.down
Aux Control	Rocker switch
Aux Connectors	3 Pins screw terminal blocks Dry point 5A 250VAC
Lens Control	Slide switch Zoom (Tilt/Wide) Focus(Near/Far) Iris(Open/Close)
Lens Connectors	6 Pins screw terminal blocks Zoom (+/-) Focus(+/-) Iris(+/-)
Lens Velocity	Output DC Voltage 6V ~ 12V 200mA
Operating Temp.	-10°C ~ 60°C
Power Lamp	Red LED
Constructions	Steel Gray enamel finish
Power Consumption	15W
Dimensions	218(W) x 44(H) x 97(D)mm
Weight	1.8kgs

PTZ 3056
6CH PTZ Controller



	PTZ3056
Lens Control	Paddle switcher control of IRIS, FOCUS, ZOOM
Pan and Tilt	Single "joystick" control
Autopan	Slide switch (MAN / OFF / AUTO)
Power Consumption	8.5W
Input Voltage	AC 117V / 220V (50Hz / 60Hz)
Output Voltage	AC 24V / 117V / 220V
Lens Output Voltage	±6V ~ ±12V DC
Lens Connector	Screw terminal-detachable
Pan / Tilt Connectors	8P mike connector (pan / tilt)
Zoom Lens Connectors	6P mike connector
Operating Temp.	-5°C ~ 60°C
Constructions	Steel, with black baked enamel finish
Dimension	438(W) x 44(H) x 245(D) mm

SOLE AGENT: