

PAN-TILT-ZOOM CONTROLLER (PTZ-AU50E)

- Multi-function keyboard
- Support RS485 and RS232 communication
- RJ45 connector and terminal block for RS485
- Speed level adjustable
- Designate part of image swapping function
- Directly control full camera functions



PTZ-AU50ES SPECIFICATIONS	
CAMERA TYPES	Speed dome (all functions)
ON SCREEN DISPLAY	All functions
ZOOM	All lens functions
COMMUNICATION BETWEEN CAMERA & CONTROLLER	Port to multi-port and half duplex function
BAUD RATES	2400, 4800, 9600 Bps
SIGNAL	RS-485 Multi-port Half Duplex
COMPATIBLE PROTOCOLS	Pelco-D , Pelco-P
NUMBERS OF SPEED DOMES CONTROLLABLE	128
POWER INPUT	DC Jack
RS485 INPUT	RJ-45 connector
INPUT VOLTAGE	12V DC (-15/+50%)
POWER CONSUMPTION	3 Watts
APPROVALS	CE and FCC
EFFECTIVE RANGE	1200 meters (max)
POWER SUPPLY / ENVIRONMENT/ MECHANISM	
DIMENSION	330(W) x 190(H) x 43(D)mm
WEIGHT	1106g
OPERATING TEMPERATURE	0°C to +40°C
STORAGE TEMPERATURE	-10 to +60C
HUMIDITY	10%~90% RH, condensation

SOLE AGENT: