

EAP-3660 is a small form factor wireless product. It is stylish and looks like a smoke detector on the ceiling. EAP-3660 is a Wireless Access Point / Repeater / WDS that operates seamlessly in the 2.4 GHz frequency spectrum supporting the 802.11b (2.4GHz, 11Mbps) and faster 802.11g (2.4GHz, 54Mbps) wireless standards. It's the best way to add wireless capability to your existing wired network, or to add bandwidth to your wireless installation.



EAP-3660 features high transmitted output power and high receivable sensitivity along with antenna diversity. High output power and high sensitivity can extend range and coverage to reduce the roaming between Access Points to get a more stable wireless connection. It also reduces the expense of equipment in the same environment.

To protect your wireless connectivity, it can encrypt all wireless transmissions through 64/128-bit WEP data encryption and also supports WPA/WPA2. The MAC address filter lets you select exactly which stations should have access to your network. In addition, the User Isolation function can protect the private network between client users.

The attractive design, high performance, and array of features make EAP-3660 a suitable wireless solution for your residence or office.

Package Content

- 1* 802.11b/g Client Bridge (EAP-3660)
- 1* 12V/1A Power Adapter
- 1* CAT5 UTP Cable
- 1*QIG
- 1*CD (User's Manual)

Jia Ying Trading Pte Ltd

1 Rochor Canal Road #02-67/ 69/ 34-37 Sim Lim Square Singapore 188504

Tel: +65-6336 0404 Fax: +65-6338 0404

Website: www.jiaying.com Email: jiaying@singnet.com.sg / email@jiaying.com.sg

Features	Benefits
High Speed Data Rate Up to 54Mbps	Capable of handling heavy data payloads such as MPEG video streaming
High Output Power up to 28 dBm	Extended excellent Range and Coverage (fewer APs)
IEEE 802.11b/g Compliant	Fully Interoperable with IEEE 802.11b/IEEE802.11g compliant devices
Embedded Antenna	Users won't see antenna in your building environment
Point-to-point, Point-to-multipoint Wireless Connectivity	Let users transfer data between two buildings or multiple buildings
WDS (Wireless Distributed System)	Make wireless AP and Bridge mode simultaneously as a wireless repeater
Universal Repeater	The easiest way to expand your wireless network's coverage
Support Multi-SSID function (4 SSID) in AP mode	Allow clients to access different networks through a single access point and assign different policies and functions for each SSID by manager
Diversity support	Enhance the traffic signal
Bandwidth selection	Using different bandwidth to reach varied distance
WPA2/WPA/ IEEE 802.1x support	Powerful data security
MAC address filtering in AP mode(up to 50)	Ensures secure network connection
User isolation support (AP mode)	Protect the private network between client users.
Power-over-Ethernet (IEEE802.3af)	Flexible Access Point locations and cost savings
Keep personal setting	Keep the latest setting when firmware upgrade
SNMP Remote Configuration Management	Help administrators to remotely configure or manage the Access Point easily.
QoS (WMM) support	Enhance user performance and density

Features	Benefits
High Speed Data Rate Up to 54Mbps	Capable of handling heavy data payloads such as MPEG video streaming
High Output Power up to 28 dBm	Extended excellent Range and Coverage (fewer APs)
IEEE 802.11b/g Compliant	Fully Interoperable with IEEE 802.11b/IEEE802.11g compliant devices
Embedded Antenna	Users won't see antenna in your building environment
Point-to-point, Point-to-multipoint Wireless Connectivity	Let users transfer data between two buildings or multiple buildings
WDS (Wireless Distributed System)	Make wireless AP and Bridge mode simultaneously as a wireless repeater
Universal Repeater	The easiest way to expand your wireless network's coverage
Support Multi-SSID function (4 SSID) in AP mode	Allow clients to access different networks through a single access point and assign different policies and functions for each SSID by manager
Diversity support	Enhance the traffic signal
WPA2/WPA/ IEEE 802.1x support	Powerful data security
MAC address filtering in AP mode(up to 50)	Ensures secure network connection
User isolation support (AP mode)	Protect the private network between client users.
Power-over-Ethernet (IEEE802.3af)	Flexible Access Point locations and cost savings
Keep personal setting	Keep the latest setting when firmware upgrade
SNMP Remote Configuration Management	Help administrators to remotely configure or manage the Access Point easily.
QoS (WMM) support	Enhance user performance and density

Technical Specifications

• Hardware Specifications

➤ Hardware Summary

Expansion Slots	N/A
Physical Interface	<ul style="list-style-type: none"> • LAN: One 10/100 Fast Ethernet RJ-45 • Reset Button • Power Jack
LEDs Status	<ul style="list-style-type: none"> • Power/ Status • LAN (10/100Mbps) • WLAN (Wireless Connection)
Power Requirements	<ul style="list-style-type: none"> • Power Supply: 90 to 240 VDC ± 10%, 50/60 Hz (depends on different countries) • Active Ethernet (Power over Ethernet, IEEE802.3af)- 48 VDC/0.375A • Device: 12V/1A
Regulation Certifications	FCC Part 15/UL, ETSI 300/328/CE

➤ Housing Look



➤ RF Specification

Frequency Band	2.400 ~ 2.484 GHz
Media Access Protocol	Carrier sense multiple access with collision avoidance (CSMA/CA)
Modulation Technology	<ul style="list-style-type: none"> OFDM: BPSK, QPSK, 16-QAM, 64-QAM DBPSK, DQPSK, CCK
Operating Channels	11 for North America, 14 for Japan, 13 for Europe
Receive Sensitivity (Typical)	<ul style="list-style-type: none"> IEEE802.11g 6Mbps@ -92dBm 54Mbps@ -74dBm IEEE802.11b 1Mbps@ -97dBm 11Mbps@ -89dBm
Available transmit power	<ul style="list-style-type: none"> IEEE802.11g 26dBm@6~24 Mbps 25dBm@36 Mbps 23dBm@48 Mbps 22dBm@54Mbps IEEE802.11b 27dBm@1 ~ 11Mbps
Antenna	Directional Embedded antenna Peak Gain = 6 dBi

• Software Features

➤ Setting

Topology	Infrastructure/Ad-Hoc
Operation Mode	Access Point/Repeater/WDS
LAN	<ul style="list-style-type: none"> DHCP Server DHCP Client

VPN	VPN pass-through (PPTP, L2TP, IPSEC)
Wireless	<ul style="list-style-type: none"> Wireless Mode – 11b / 11g / Disable Channel Selection (Setting varies by Country) Transmission Rate <ul style="list-style-type: none"> ➤ 11 b/g: 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1 in Mbps Transmit power (4 levels) Antenna Diversity
Security	<ul style="list-style-type: none"> WEP Encryption-64/128/152 bit WPA Personal (WPA-PSK using TKIP or AES) WPA Enterprise (WPA-EAP using TKIP) 802.1x Authenticator Hide SSID in beacons Multiple SSID with 802.1q VLAN tagging (up to 4 SSIDs) MAC Filter L2 isolation Wireless STA (Client) connected list
QoS	<ul style="list-style-type: none"> WMM

➤ Management

Configuration	Web-based configuration (HTTP)/Telnet
Firmware Upgrade	<ul style="list-style-type: none"> Upgrade firmware via web-browser Keep latest setting when f/w update
Administrator Setting	<ul style="list-style-type: none"> Administrator password change
Reset Setting	<ul style="list-style-type: none"> Reboot Reset to Factory Default
System monitoring	Status, Statistics and Event Log
SNMP	V1, V2c
MIB	MIB I, MIB II (RFC1213) and Private MIB
Backup & Restore	Settings through Web

• **Environment & Physical**

Temperature Range	<ul style="list-style-type: none">• Operating: 0°C to 45°C (32°F to 113°F)• Storage: -20°C to 70°C (-4°F to 158°F)
Humidity (non-condensing)	5% ~ 95% typical
Dimensions	Diameter: 120mm Height: 50mm
Weight	280g