



Laser Multi-Function Printer (A4) Monochrome Print

Multi-Function Printer KX-MB2168ML

| | | | |
|------------------------|--|--|---|
| General | Printing Process | | Laser |
| | Recording Paper Size (Simplex) | | -Input Tray: A4, LTR, LGL, B5(JIS/ISO), Folio (216 x 330 mm), Oficio (216 x 340 mm), 16K -Manual tray: A5, A4, LTR, LGL, B5(JIS/ISO), Folio (216 x 330 mm), Oficio (216 x 340 mm), 16K, Envelope #10/DL /YOUKEI #4/CHOUKEI #3/CHOUKEI #4, Custom (W: 210-216 mm, L: 279-356 mm) |
| | Recording Paper Capacity* ¹ | | Max: 251 sheets [Standard input tray: 250 sheets / Manual tray: 1 sheet] |
| | Paper Output Capacity | | 100 sheets |
| | ADF | Capacity | 35 sheets |
| | | Document size | A4, LTR,LGL, B5(JIS),B5(ISO), Folio (216 x 330 mm), Oficio (216 x 340 mm), 16K |
| | LCD Display | | 16 digits / 2 lines with back-light |
| | Memory Size | | 64 MB |
| | Monthly duty | Average | 1,200 pages |
| | | Maximum | 12,000 pages |
| | Power Consumption | | Maximum: Approx. 1000 W Copy: Approx. 500 W, Ready: Approx. 65 W Sleep: Less than 3.3 W* ² |
| | Noise level | Standby | Less than 25 dBA* ³ |
| | | Copying | Less than 52 dBA* ³ |
| | Computer Interface | | Wi-Fi (IEEE802.11b/g/n), 100Base-TX/10Base-T, USB2.0 |
| Dimensions (W x D x H) | | 410 x 400 x 320 mm (Including handset: 447 x 400 x 320 mm) | |
| Weight | | Approx. 12 kg | |
| Printer | Print Speed | Up to 26 ppm (A4) | |
| | Duplex Printing | Yes (A4, LTR, LGL, 216 x 330 mm, 216 x 340 mm) | |
| | Duplex Productivity (A4) | 92 % (24 ppm) | |

| | | |
|---------|-------------------------|--|
| | Print Resolution | Up to 600 x 600 dpi |
| | First Print Time | 8.5 s (from standby) |
| | Emulation | GDI |
| | Supported OS | Windows® XP, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1 Windows Server® 2008, Windows Server® 2012, Mac OS X 10.5 - 10.9, Linux®*4 |
| Copier | Copy Speed*5 | Up to 26 cpm (A4) |
| | Copy Resolution | Up to 600 x 600 dpi |
| | Multi-Copy | 99 pages |
| | First Copy Time | 10.5 s (ADF) |
| | Reduction / Enlargement | 25 % - 400 % (1 % step) |
| | Copy Function | Quick ID, N-in-1, Separate N-in-1, Poster, Image Repeat, Edge/Margin |
| Scanner | Colour / Mono Scan | Yes / Yes |
| | Scan Resolution | Optical: Up to 600 x 1200 dpi (Flatbed) / Interpolated: Up to 19200 x 19200 dpi |
| | Scan Function | Scan to PC/Email Address/FTP/SMB |
| | Supported OS | Windows® XP, Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Mac OS X 10.5 - 10.9, Linux®*4 |
| Fax | Modem Speed | 33.6 kbps - 2.4 kbps with automatic fallback |
| | Memory Size | Total 3 MB (Reception: Approx. 80 pages*6, Transmission: Approx. 150 pages*6) |
| | Address book | 100 |
| | Fax / Tel Switch | Yes |
| | Fax to Email | Yes |
| | Web Fax Preview | Yes |

| | |
|-----------------|--|
| Toner Cartridge | KX-FAT472E (2,000 pages*7) KX-FAT472E-T (2,000 pages*7 x 3) |
| Drum Cartridge | KX-FAD473E (10,000 pages) |
| Note | <p>*1 Depending on the type of paper.</p> <p>*2 When only USB interface is connected and LAN is OFF mode. Power consumption in sleep mode depends on machine condition.</p> <p>*3 Sound Pressure Level based on ISO7779 bystander position. It depends on the measuring method.</p> <p>*4 Supported Linux distribution: Red Hat® Enterprise Linux® Desktop 5/6, Ubuntu® 10/11/12/13/14. Driver is provided via web download.</p> <p>*5 Continuous copy of a single original.</p> <p>*6 Based on the ITU-T No. 1 Test Chart in standard resolution.</p> <p>*7 ISO/IEC 19752 standard.</p> |

Available at:

JIA YING TRADING PTE LTD

1 Rochor Canal Road #02-67,69, 34-37 Sim Lim Square, Singapore 188504
Tel: 6336-0404 Fax: 6338 0404 jiaying@singnet.com.sg www.jiaying.com