

SN-258 PLUS

Long Range Cordless Phone



Ultra Long Range
Lets you take the handset farther from the base unit



Group Call
Allows you to talk in a group



Walkie-Talkie
Half-Duplex talk between two handsets



Scrambler
Keeps conversations private and prevent eavesdropping.



Multiple Handsets
The base unit can accommodate up to 15 handsets.



Lock keypads
Suspends dialing



Multiple Base units
The handset can accommodate up to 4 base units



Multiple Channel Access
Auto scan 240 channels to avoid interference

Features:

- * Multi-channel access with auto-scan
- * Multi-handset system (up to 15)
- * Multi-base system (up to 4, optional)
- * Walkie-talkie between handsets (up to 15 handsets)
- * Half-Duplex group call
- * Two-way paging and hands-free intercom
- * 9-set memory dial for each handset (20 digits)
- * Last number redial
- * ToneJPulse dialling mode selectable
- * Change channel during conversation
- * Keypad lock function
- * Flash time programmable
- * Ring volume adjustable
- * Voice volume adjustable
- * Music on hold
- * Touch any key answer
- * Handset with power saving circuit
- * Low battery alert and indicator
- * Out of range alert
- * Battery power status display
- * Fast charge
- * Built-in noise cancellation circuit (Compander)
- * Built-in voice security and mutation circuit (Scrambler)
- * Auto answer and auto hang up,
- * Transferring a call among handsets.
- * Hands-free kit for handset (optional)
- * Separate charger (optional)
- * Vibration alert (Vibration version only)

Base Unit		Handset
Transmitter		
Frequency	388MHz	262MHz
Output power	1W	350mW
Spurious emission	55dBc	55dBc
Current consumption: Stand-by	100mA	7~12mA
Current consumption: Talk	600mA	350mA
Receiver		
Frequency	262MHz	388MHz
Sensitivity at 12dB SINAD (CCITT)	-122dBm	-122dBm
Adjacent channel rejection	50dBc	50dBc
Spurious response	55dBc	55dBc
Power source	AC 110V/60Hz AC 220V/50Hz DC 12V	4.8V/750mAh Ni-MH Battery
Dimension	WxDxH(m/m) 195x145x51	LxWxH(m/m) 150x53x32
Weight	500g	210g